



DESIGN

Modern, straight contours and minimal overlaps blend seamlessly into the minimalist construction trend.



THERMAL INSULATION

Maximum performance through the five- or six-chamber profile constructions with two or three sealing levels.



SUSTAINABILITY

A high recycled content in the inner core ensures a resource-saving use of materials.



SYSTEM COMPATIBILITY

Perfect compatibility with other Schüco products for seamless integration.



DIVERSE COLORS

A wide range of color options for individual design and customization.



RESILIENCE

Robust, long-lasting construction for maximum stability and durability.

PROFILE SYSTEM
FOCUSING

Suitable for:



BREEAM®



TECHNICAL DATA

Basic depth outer frame	70 mm
Basic depth vent	76 mm
Uw value	0,82 W/(m ² K)*
Glass thickness outer frame	10–48 mm
Glass thickness vent	16–52 mm
Max. vent width**	1500 mm
Max. vent height**	2600 mm
Max. sound reduction index Rwp	48 dB(A)
Air permeability	Class 4
Watertightness	Class 9A
Burglar resistance	up to RC 2
Wind load resistance	Class B5
Max. vent weight	120 kg

Operating forces Class 1

Mechanical strength Class 4, DIN EN 13115

Proof of durability DIN EN 12400, Class 2

Drainage levels 2 at AS, 3 at MD

* in version with Ug 0.5 glazing

** Maximum dimensions only possible with correct height-to-width ratio

More info:

[https://www.schueco.com/de-en/architects/
products/windows/pvc-u/focusing](https://www.schueco.com/de-en/architects/products/windows/pvc-u/focusing)

