


# Stulpfenster mittig 150 kg, Basisbeschlag, Drehstulp



		Pos.			Pos.	
 <b>BASIC</b>	2	E1	4.1	 <b>OPTION</b>	DB.SE	6.2.1
	1	E1.SE	4.2		RADB.K.SE ...RS / LS	6.2.2
	1	FLS.SE	5.7a		DLS.K.SE.9-13	8.1
	1	FL.SE.1	5.7b		DLK.SE ... RS / LS	8.2
	1	EL.K.SE ...RS / LS	5.7c		RT.DFE-TF.E.S	10.6
	1	APK.SE ...RS/LS	5.7d			
	3	SBAK ...	11.1			

		Pos. 5.3	9.2	11.1	
 <b>FFB</b>	380 - 480	OS.SE.550	+ E3 *		
	481 - 550	OS.SE.550			
	551 - 800	OS.SE.800			
	801 - 1025	OS.SE.1025-1	M.500-1	+ 2	
	1026 - 1250	OS.SE.1250-1	M.500-1	+ 2	
	1251 - 1475	OS.SE.1250-1	+MK.250-0	M.750-1	+ 2
	1476 - 1725	OS.SE.1250-1	+MK.250-1 +ZSR	MK.500-1 +M.500-1	+ 4

		Pos. 3.1	9.1	9.2	11.1
 <b>FFH</b>	561 - 710	GASM.800*			
	711 - 950	GASM.1050-1		M.250-1	+ 1
	951 - 1200	GASM.1400-1		M.500-1	+ 1
	1201 - 1400	GASM.1400-2		M.750-1	+ 1
	1401 - 1650	GASM.1800-2	MK.500-1	+ M.500-1	+ 2
	1651 - 1800	GASM.1800-2	MK.750-1	+ M.500-1	+ 2
	1801 - 1900	GASM.2300-3	MK.750-1	+ M.500-1	+ 2
	1901 - 2150	GASM.2300-3	MK.750-1	+ M.750-1	+ 2
	2151 - 2300	GASM.2300-3*	MK.750-1	+ MK.500-1	+M.500-1

max. 150 kg	max. 3,0m <sup>2</sup>	max. 1725 mm	max. 2776 mm / 2860 mm	2 : 1
----------------	---------------------------	-----------------	------------------------------	-------

\* ?

...16-18